SAFETY DATA SHEET

125 ONE HOUR CAULK - ALL COLOURS

Page 1 Issued: 11/05/2004 Revision No: 2

1. IDENTIFICATION OF T	HE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING
	125 ONE HOUR CAULK - ALL COLOURS
Product code:	125 - all colours
	EVERBUILD BUILDING PRODUCTS LTD
	SITE 41, KNOWSTHORPE WAY
	CROSS GREEN INDUSTRIAL ESTATE
	LEEDS
	WEST YORKSHIRE
	LS9OSW
	ENGLAND
	Tel: 0044 113 240 3456
	Fax: 0044 113 240 0024
COMPOSITION / INFOR	RMATION ON INGREDIENTS
	Contains a plasticised water based acrylic emulsion with dense fillers, very minor amounts of
Contains.	
	white spirits (ca. 1%), dispersants, bocides, and acrylic associate thickeners.
3. HAZARDS IDENTIFICAT	
	No significant hazard.
4. FIRST AID MEASURES (
	There may be mild irritation at the site of contact.
	There may be irritation and redness.
_	There may be irritation of the throat.
	No symptoms.
4. FIRST AID MEASURES (ACTION)	
	Wash immediately with plenty of soap and water.
	Bathe the eye with running water for 15 minutes.
-	Wash out mouth with water.
5. FIRE-FIGHTING MEASURES	
-	In combustion emits toxic fumes.
Protection of fire-fighters:	
	and eyes.
<u>6. ACCIDENTAL RELEASE</u>	
-	Refer to section 8 of SDS for personal protection details.
-	Do not discharge into drains or rivers.
Clean-up procedures:	Wash the spillage site with large amounts of water.

SAFETY DATA SHEET

125 ONE HOUR CAULK - ALL COLOURS

Page 2

7. HANDLING AND STORA	AGE	
Storage conditions:	Store in cool, well ventilated area. Store in original containers between +5 and +25 °C. Storage	
	outside these paramaters will dramatically reduce shelf life and invalidates all product	
	warrenties.	
Suitable packaging:	Must only be kept in original packaging.	
8. EXPOSURE CONTROLS / PERSONAL PROTECTION		
Respiratory protection:	Respiratory protection not required.	
Hand protection:	Protective gloves.	
Eye protection:	Safety glasses. Ensure eye bath is to hand.	
Skin protection:	Protective clothing.	
9. PHYSICAL AND CHEMICAL PROPERTIES		
State:	Paste	
Colour:	Various	
Odour:	Barely perceptible odour	
Evaporation rate:	Slow	
Oxidising:	Non-oxidising (by EC criteria)	
Solubility in water:	Miscible	
Viscosity:	Highly viscous	
Viscosity value:	250-350	
Viscosity test method:	x 1000 cps - Brookfield HBDV2+, spindle S70, 10rpm @ 20°C	
Boiling point/range°C:	100	
Flammability limits %: lower:	N/A	
upper:	N/A	
Autoflammability°C:	N/D	
Vapour pressure:	as water	
Relative density:	1.68	
pH:	8.5-9.9	
10. STABILITY AND REACTIVITY		
Stability:	Stable under normal conditions.	
Conditions to avoid:	Heat.	
Materials to avoid:	Strong oxidising agents. Strong acids.	
Haz. decomp. products:	In combustion emits toxic fumes.	
11. TOXICOLOGICAL INFO	DRMATION	
Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.	
12. ECOLOGICAL INFORM	IATION	
Persistence and degradability:	No data available.	
Bioaccumulative potential:	No data available.	
	front 1	

SAFETY DATA SHEET

125 ONE HOUR CAULK - ALL COLOURS

Other adverse effects: No data available.

13. DISPOSAL CONSIDERA	ATIONS
Disposal operations:	Dispose of according to local or national legislation
NB:	The user's attention is drawn to the possible existence of regional or national regulations
	regarding disposal.
14. TRANSPORT INFORMA	
ADR / RID	
UN no:	
Shipping name:	- "NOT SUBJECT TO ADR"
	NOT SUBJECT TO ADK
IMDG / IMO	
UN no:	-
IATA / ICAO	
UN no:	-
15. REGULATORY INFORMATION	
Hazard symbols:	No significant hazard.
Note:	The regulatory information given above only indicates the principal regulations specifically
	applicable to the product described in the safety data sheet. The user's attention is drawn to
	the possible existence of additional provisions which complete these regulations. Refer to all
	applicable national, international and local regulations or provisions.
16. OTHER INFORMATION	
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and shall
	be used only as a guide. This company shall not be held liable for any damage resulting from
	handling or from contact with the above product.

Page 3